ETHERMA°
EFFICIENT. ELECTRIC. HEATING.

PRODUCT DATASHEET

Type: Stapaflex-FPR
Art. Nr.: 30011

0 912005 417073

Short description
Installation hose, Stapaflex, asphalt installation, DN 20

Product Description
Armored installation hose for laying sensors and connecting lines in asphalt pavements. The hose is resistant to the high temperatures during the application of asphalt pavement.

ETIM characteristics

Material	Aluminium
Material quality	Other
Surface protection	Untreated
Quality of surface coating	Other
Surface polished	✖
Surface brushed	✖
Model	Pliable corrugated
Connection 1	Other
Connection 2	Other
Colour	Grey
Flush-mounted installation	✔
Surface mounting	✖
Suitable for concrete installation	✔
Machine and systems installation	✔
Suitable for underfloor installation (bitumen, hot asphalt)	✔
Suitable for underfloor installation (screed)	✔
Outdoor installation	✔
Installation on wood	✔
Suitable for hollow wall installation	✔
Suitable for underground installation	✔

Inner diameter	16 Millimetre
Outer diameter	20 Millimetre
Operating temperature	220|220 Degrees celsius

Created on: 27/11/2023

ETHERMA Elektrowärme GmbH
Landesstrasse 16
A-5302 Henndorf am Wallersee
Tel.: +43 6214 / 76 77
Mail: office@etherma.com
Web: www.etherma.com

ETHERMA Deutschland GmbH
Bahnhofstraße 40
D-48599 Gronau
Tel.: +49 2562 / 81 97 00
Mail: office.de@etherma.com
Web: www.etherma.com